

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @attrender (#36), rename @lang to @languageOElement and relax data type from NMTOKEN to token (#53; #59), rename @script to @scriptOElement and relax data type from NMTOKEN to token (#59; #59), add @target with new data type IDREFS (#31), add option to include attributes from any other namespace (#28)</p> <p>..Reference attributes added (for elements that have existed in EAD3 already) ..Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>															<p>Attributes in EAD 4.0</p>					<p>Content models in EAD 4.0</p>				
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	..Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOElement, scriptOElement	conventionDeclarationReference, maintenanceEventReference, sourceReference	localType, localTypeDeclarationReference	valueURI, vocabularySource, URI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduced mixed content (reference, span, referringString)	formatting-Extension	Context specific sub-elements	Shared						
abbr	shortCode (referringString)	Y			Rename to shortCode in conventionDeclaration, localTypeDeclaration, and rightsDeclaration Remove @expan	#32	Y	Y							Y	Y				Y						
abstract	abstract	Y	Y	Y	Add reference, span, and referringString as optional and repeatable sub-elements Remove abbr, emph, expan, foreign, lb, pt, ref, persname, corpname, famname, geogname, name, occupation, subject, genreform, function, title, date, footnote, num, quote Remove @encodinganalog and @label	#47; #57; #40; #53; #71; #36; #37	Y	Y	Y	Y					Y	Y	Y			Y (requires update in EAC-CPF)						
accessrestrict	accessConditions	Y	Y	Y	Rename to accessConditions Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Add dateRange as an optional, not repeatable sub-element Remove nesting, i.e. remove accessrestrict as sub-element Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog	#60; #57; #59; #62; #68; #49; #74; #37			Y	Y	Y				Y			Y	Y							
accruals	accruals	Y	Y	Y	Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove accruals as sub-element Remove @encodinganalog	#57; #63; #62; #37	Y	Y	Y	Y					Y			Y	Y							
acqinfo	sourceOfAcquisition	Y	Y	Y	Rename to sourceOfAcquisition Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove acqinfo as sub-element Remove @encodinganalog	#57; #59; #52; #66; #48; #37	Y	Y	Y	Y					Y			Y	Y							
address	address	Y	Y		Apply camelCoding to sub-element addressLine Add @localType and @localTypeDeclarationReference	#42	Y	Y	Y	Y					Y					Y						
addressline	addressLine	Y	Y		Apply camelCasing Add reference, span, and referringString as optional and repeatable sub-elements Remove abbr, emph, expan, foreign, lb, pt, ref Add optional attribute @addressLineType with data type token Remove @localType	#42; #70; #53; #40; #1	Y	Y	Y	Y				Y	Y	Y				Y						
agencycode	agencyCode	Y			Add @status Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog and @localType	#32; #37	Y	Y			Y			Y	Y	Y				Y						
agencyname	agencyName	Y			Make sure all instances of agencyName appear before any instances of otherAgencyCode (if existing) Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog and @localType	#32; #37; #49	Y	Y			Y				Y	Y				Y						
agent	agent	Y	Y		Remove option for agent to include text itself Add agentName as a required, repeatable sub-element Add agentRole, agentType, relationType, placName as optional, repeatable sub-elements Add an optional choice of date, dateRange or dateSet Add descriptiveNote as optional, not repeatable sub-element Add @localType along with @localTypeDeclarationReference as optional attributes Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog	#58; #37	Y	Y	Y	Y	Y				Y				Y	Y						
	agentName				Add agentName Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y	Y				Y	Y					Y (requires update in EAC-CPF)					
	agentRole				Add agentRole Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y	Y				Y	Y					Y (requires update in EAC-CPF)					
	agents				Add agents Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y					Y				Y							
agenttype	agentType	Y	Y		Remove @value Remove @encodinganalog Add optional attribute @localType along with @localTypeDeclarationReference Add optional attributes @valueURI, @vocabularySource, @vocabularySourceURI	#32; #37; #49	Y	Y	Y	Y	Y				Y	Y					Y (requires update in EAC-CPF)					
altformavail	formAvailable	Y	Y	Y	Integrate with the new entity element formAvailable and apply camelCasing in this context Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Add relations as an optional, not repeatable sub-element Remove nesting, i.e. remove altformavail as sub-element Add @valueURI, @vocabularySource, @vocabularySourceURI Add @coverage Remove @encodinganalog	#65; #69; #57; #59; #62; #49; #74; #37	Y	Y	Y	Y	Y			Y	Y	Y			Y	Y						

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @attrender (#3), rename @lang to @languageOfElement and relax data type from NMTOKEN to token (#5), rename @script to @scriptOfElement and relax data type from NMTOKEN to token (#5), add @target with new data type IDREFS (#31), add option to include attributes from any other namespace (#28)</p> <p>--Reference attributes added (for elements that have existed in EAD3 already) --Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>																			
		<p>localType changes (for element that have existed in EAD3 already and include @localType there) - Apply camelCasing to @localType (#43) - Add the parallel attribute @localTypeDeclarationReference with data type IDREFS (#43)</p>				Attributes in EAD 4.0										Content models in EAD 4.0					
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOfElement, scriptOfElement	conventionDeclarationReference, maintenance-EventReference, sourceReference	localTypeDeclarationReference	valueURI, vocabularySource, vocabularySourceURI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduced mixed content (reference, span, referringString)	formatting-Extension	Context specific sub-elements	Shared	
appraisal	appraisal	Y	Y	Y	Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove appraisal as sub-element Remove @encodinganalog	#57; #59; #92; #37	Y	Y	Y	Y					Y			Y	Y		
archdesc	archDesc	Y	Y	Y	Apply camelCasing Add optional attributes @valueURI, @vocabularySource, @vocabularySourceURI Make @level optional, remove its predefined values and remove @otherlevel Remove @relatedencoding and @encodinganalog Add optional, not repeatable sub-elements agents, formsAvailable, functions Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, userrestrict to useConditions Apply camelCasing to biogHist, custodiHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalloc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of archDesc and into formsAvailable Move legalStatus out of archDesc and into identificationData Rename desc to descriptionOfComponents and remove repeatability Remove archref, see Transformations tab for more details	#72; #1; #28; #37; #68; #66; #50; #49; #57; #65; #63; #5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y				Y	
archref	(reference)					#46															
arrangement	arrangement	Y	Y	Y	Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove arrangement as sub-element Remove @encodinganalog	#57; #59; #92; #37	Y	Y	Y	Y					Y			Y	Y		
author	(agent)					#27															
bibliography	publicationNote	Y	Y	Y	Rename to publicationNote and apply camelCasing in this context Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove bibliography as sub-element Add relations as optional, not repeatable sub-element Remove archref and bibref as direct sub-elements Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog	#57; #59; #92; #69; #49; #93; #74; #46; #37	Y	Y	Y	Y					Y			Y	Y		
bibref	(reference)					#46															
bioghist	biogHist	Y	Y	Y	Apply camelCasing Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove bioghist as sub-element Remove @encodinganalog	#57; #59; #92; #49; #37	Y	Y	Y	Y					Y			Y	Y	Y	
blockquote	(formattingExtension)					#52															
c	c	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, userrestrict to useConditions Apply camelCasing to biogHist, custodiHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalloc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c and into formsAvailable Move legalStatus out of c and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #28; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y				Y	

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @attrender (#3), rename @lang to @languageOIElement and relax data type from NMTOKEN to token (#5), rename @script to @scriptOIElement and relax data type from NMTOKEN to token (#5), #50, add @target with new data type IDREFS (#31), add option to include attributes from any other namespace (#28)</p> <p>..Reference attributes added (for elements that have existed in EAD3 already) ..Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>																		
		<p>localType changes (for element that have existed in EAD3 already and include @localtype there) - Apply camelCasing to @localType (#43) - Add the parallel attribute @localTypeDeclarationReference with data type IDREFS (#43)</p>				<p>Attributes in EAD 4.0</p>										<p>Content models in EAD 4.0</p>				
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	..Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOIElement, scriptOIElement	conventionDeclarationReference, maintenanceEventReference, sourceReference	localType, localTypeDeclarationReference	valueURI, vocabularySource, URI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduce mixed content (reference, span, referringString)	formatting-Extension	Context specific sub-elements	Shared
c01	c01	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c01 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c01 and into formsAvailable Move legalStatus out of c01 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c02	c02	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c02 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c02 and into formsAvailable Move legalStatus out of c02 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c03	c03	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c03 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c03 and into formsAvailable Move legalStatus out of c03 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c04	c04	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c04 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c04 and into formsAvailable Move legalStatus out of c04 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c05	c05	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c05 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c05 and into formsAvailable Move legalStatus out of c05 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @attrender (#3), rename @lang to @languageOIElement and relax data type from NMTOKEN to token (#5), rename @script to @scriptOIElement and relax data type from NMTOKEN to token (#5), add @target with new data type IDREFS (#31) add option to include attributes from any other namespace (#28)</p> <p>..Reference attributes added (for elements that have existed in EAD3 already) ..Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>																		
		<p>localType changes (for element that have existed in EAD3 already and include @localtype there) - Apply camelCasing to @localType (#43) - Add the parallel attribute @localTypeDeclarationReference with data type IDREFS (#43)</p>				<p>Attributes in EAD 4.0</p>										<p>Content models in EAD 4.0</p>				
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	..Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOIElement, scriptOIElement	conventionDeclarationReference, maintenanceEventReference, sourceReference	localType, localTypeDeclarationReference	valueURI, vocabularySource, URI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduce mixed content (reference, span, referringString)	formatting-Extension	Context specific sub-elements	Shared
c06	c06	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c06 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c06 and into formsAvailable Move legalStatus out of c06 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c07	c07	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c07 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c07 and into formsAvailable Move legalStatus out of c07 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c08	c08	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c08 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c08 and into formsAvailable Move legalStatus out of c08 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c09	c09	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c09 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c09 and into formsAvailable Move legalStatus out of c09 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c10	c10	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c10 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, usersrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c10 and into formsAvailable Move legalStatus out of c10 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #68; #66; #50; #67; #55; #69; #5	Y	Y	Y		Y		Y	Y	Y				Y	

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @attender (#3), rename @lang to @languageOIElement and relax data type from NMTOKEN to token (#5), rename @script to @scriptOIElement and relax data type from NMTOKEN to token (#30, #50), add @target with new data type IDREFS (#31), add option to include attributes from any other namespace (#28)</p> <p>..Reference attributes added (for elements that have existed in EAD3 already) ..Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>				<p>Attributes in EAD 4.0</p>										<p>Content models in EAD 4.0</p>				
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	..Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOIElement, scriptOIElement	conventionDeclarationReference, maintenanceEventReference, sourceReference	localType, localTypeDeclarationReference	valueURI, vocabularySource, URI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduced mixed content (reference, span, referringString)	formatting-Extension	Context specific sub-elements	Shared
c11	c11	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c11 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, userrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c11 and into formsAvailable Move legalStatus out of c11 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #48; #56; #50; #57; #55; #58; #5	Y	Y	Y		Y		Y	Y	Y				Y	
c12	c12	Y	Y		Add agents, formsAvailable, functions, and places as optional, not repeatable sub-elements of c12 Rename did to identificationData, accessrestrict to accessConditions, acqinfo to sourceOfAcquisition, altformavail to formAvailable, bibliography to publicationNote, controlaccess to subjectHeadings, odd to otherDescriptiveInfo, phystech to physicalOrTechnicalRequirements, userrestrict to useConditions Apply camelCasing to biogHist, custodHist, filePlan, legalStatus, otherFindAid, preferCite, processInfo, relatedMaterial, scopeContent, separatedMaterial Remove index (integrated in subjectHeadings), originalstoc (integrated in formAvailable), relations (added to formAvailable, otherFindAid, publicationNote, relatedMaterial, separatedMaterial instead) Move formAvailable out of c12 and into formsAvailable Move legalStatus out of c12 and into identificationData Remove thead Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @otherlevel and @encodinganalog	#72; #1; #26; #37; #48; #56; #50; #57; #55; #58; #5	Y	Y	Y		Y		Y	Y	Y				Y	
	citedRange				Add citedRange Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y					Y	Y	Y				Y
chronilem	(formattingExtension)				Remove chronilem, see Transformations tab for more details	#52														
chronilemset	(formattingExtension)				Remove chronilemset, see Transformations tab for more details	#52														
chronilist	(formattingExtension)				Remove chronilist, see Transformations tab for more details	#52														
citation	(reference)				Remove citation, see Transformations tab for more details	#32														
colspec	(formattingExtension)				Remove colspec, see Transformations tab for more details	#52														
	contact				Add contact Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y					Y				Y	Y
	contactLine				Add contactLine Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y		Y		Y	Y	Y					Y
container	container	Y	Y	Y	Add reference, span, and referringString as optional and repeatable sub-elements Remove abbr, emph, expan, foreign, lb, pt, ref Add optional attributes @valueURI, @vocabularySource, and @vocabularySourceURI Apply camelCasing to attribute @containerid and change its data type to token Remove @encodinganalog and @label	#40; #63; #71; #36; #37	Y	Y	Y	Y	Y		Y	Y	Y		Y			
control	control	Y			Remove representation and localcontrol Move filedesc out of control and rename to findAidDesc Turn maintenancestatus and publicationstatus into optional attributes @maintenanceStatus and @publicationStatus, both with data type token Apply camelCasing to sub-elements recordid, maintenanceAgency, maintenanceHistory, conventionDeclaration, languageDeclaration, localTypeDeclaration, otherRecordid, rightsDeclaration Adapt sequence of sub-elements to recordid, maintenanceAgency, maintenanceHistory, sources, followed by the remaining sub-elements grouped (0..n) in alphabetical order Add optional attribute @detailLevel with data type token Add optional attributes @addressLineTypeEncoding, @audienceEncoding, @contactLineTypeEncoding, @coverageEncoding, @detailLevelEncoding, @descriptionOfComponentsTypeEncoding, @levelEncoding, @maintenanceEventTypeEncoding, @maintenanceStatusEncoding, @physDescStructuredTypeEncoding, @publicationStatusEncoding, @statusEncoding, @unDateTypeEncoding all with data type token and a choice between values "EASISList" or "other..Encoding" Apply camelCasing to attribute @countryEncoding, @dateEncoding, @languageEncoding (renamed from @langencoding), @repositoryEncoding, @scriptEncoding Apply camelCasing to the attribute values "otherCountryEncoding", "otherDateEncoding", "otherLanguageEncoding" (renamed from "otherLanguageEncoding"), "otherRepositoryEncoding", "otherScriptEncoding" Change value "iso639-2" in @languageEncoding to "iso639-2" and add "self-bcp-47" as another possible value Remove @relatedencodig and @encodinganalog	#32; #27; #49; #1; #28; #37	Y	Y					Y	Y	Y				Y	Y

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @attender (#36), rename @lang to @languageOfElement and relax data type from NMTOKEN to token (#53; #59), rename @script to @scriptOfElement and relax data type from NMTOKEN to token (#59; #59), add @target with new data type IDREFS (#31), add option to include attributes from any other namespace (#28)</p> <p>...Reference attributes added (for elements that have existed in EAD3 already) -Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>															<p>Attributes in EAD 4.0</p>					<p>Content models in EAD 4.0</p>				
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	...Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOfElement, scriptOfElement	conventionDeclarationReference, maintenanceEventReference, sourceReference	localType, localTypeDeclarationReference	valueURI, vocabularySource, vocabularySourceURI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduced mixed content (reference, span, referringString)	formatting-Extension	Context specific sub-elements	Shared						
controlaccess	subjectHeadings	Y	Y	Y	Rename to subjectHeadings Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Make subject a required and repeatable sub-element Remove the other access elements corpname, firmname, function, genreform, geogname, name, occupation, persname, title Remove nesting, i.e. remove controlaccess as sub-element Remove @encodinganalog	#67; #57; #59; #54; #49; #37	Y	Y	Y	Y					Y			Y	Y							
controlnote	(findAidDesc)				Remove controlnote, see Transformations tab for more details	#27																				
conventiondeclaration	conventionDeclaration	Y			Replace abbr with shortCode and citation with reference Change order of sub-elements so that reference comes first, followed by shortCode and descriptiveNote Apply camelCasing to sub-element descriptiveNote Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog and @localtype	#32; #37; #49	Y	Y			Y				Y				Y	Y						
corpname	(agent) (referringString)				Remove corpname, see Transformations tab for more details	#58; #68; #63																				
custodhist	custodHist	Y	Y	Y	Apply camelCasing Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove custodhist as sub-element Remove @encodinganalog	#57; #59; #52; #49; #37	Y	Y	Y	Y					Y			Y	Y							
dao	(formAvailable)				Remove dao, see Transformations tab for more details	#65																				
daoset	(formAvailable)				Remove daoset, see Transformations tab for more details	#65																				
date	date	Y	Y	Y	Remove abbr, emph, expan, foreign, lb, ptr, ref Replace @normal with @standardDate and add @notAfter and @notBefore Add @status with data type token Remove @encodinganalog	#4	Y	Y	Y	Y			Y	Y	Y					Y						
daterange	dateRange	Y	Y	Y	Apply camelCasing to dateRange and its sub-elements fromDate and toDate Require either fromDate or toDate to be present Require fromDate to be used before toDate if both are present	#4	Y	Y	Y	Y				Y					Y	Y						
dateset	dateSet	Y	Y	Y	Apply camelCasing to dateSet and its sub-element dateRange Replace datesingle with date as a sub-element of dateSet	#4	Y	Y	Y	Y				Y					Y	Y						
datesingle	(date)				Remove datesingle, see Transformations tab for more details	#4																				
defitem	(formattingExtension)				Remove defitem, see Transformations tab for more details	#52																				
descriptivenote	descriptiveNote	Y	Y		Apply camelCasing Remove @encodinganalog		Y	Y	Y						Y				Y	Y						
did	identificationData	Y	Y		Rename to identificationData Remove abstract from identificationData Remove dao and daoset from identificationData Remove origination and repository from identificationData Rename sub-elements didnote to identificationDataNote and langmaterial to languageOfMaterial Apply camelCasing to sub-elements materialSpec, physDescSet, physDesc, physDescStructured, physLoc, unitDate, unitDateStructured, unitId, unitTitle Add sub-element legalStatus Remove @encodinganalog	#66; #49; #57; #65; #68; #5; #37	Y	Y	Y	Y				Y					Y	Y						
didnote	identificationDataNote	Y	Y		Rename to identificationDataNote Add sub-element p (required and repeatable) to apply the same model as for descriptiveNote Remove @localtype, @encodinganalog, and @label	#66; #53; #36; #37	Y	Y	Y					Y					Y							
dimensions	dimensions	Y	Y	Y	Add reference, span, and referringString as optional and repeatable sub-elements Remove abbr, emph, expan, foreign, lb, ptr, ref Remove nested dimensions Remove @encodinganalog	#70; #40; #63; #71	Y	Y	Y	Y				Y	Y	Y										
dsc	descriptionOfComponents	Y	Y		Rename to descriptionOfComponents Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, p, list, table, and thead Rename attribute @dsctype to @descriptionOfComponentsType Remove @othersdsctype and @encodinganalog	#66; #53; #62; #1; #37	Y	Y	Y	Y				Y				Y	Y							
ead	ead	Y			Note: ead is the only element to which @target is NOT added Remove @relatedencoding Apply camelCasing to sub-element archDesc Add findAidDesc as optional and repeatable sub-element (between control and archDesc)	#31; #37; #49; #27	Y (no @target)	Y					Y	Y					Y							
edition	(findAidDesc)				Remove edition, see Transformations tab for more details	#27																				
editionstmt	(findAidDesc)				Remove editionstmt, see Transformations tab for more details	#27																				
emph	span	Y	Y		Rename to span Remove abbr, emph, expan, foreign, lb, ptr, ref Replace @render with @style	#71	Y	Y	Y	Y			Y	Y	Y					Y						
entry	(formattingExtension)				Remove entry, see Transformations tab for more details	#62																				
event	(formattingExtension)				Remove event, see Transformations tab for more details	#62																				
eventdatetime	eventDateTime	Y			Apply camelCasing to @standardDateTime and relax its data type to not be restricted to the year 2099 as the latest possible year anymore Remove @encodinganalog	#32; #37; #49	Y	Y					Y	Y	Y					Y						

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @attrender (#30), rename @lang to @languageOfElement and relax data type from NMTOKEN to token (#53; #59), rename @script to @scriptOfElement and relax data type from NMTOKEN to token (#50; #59), add @target with new data type IDREFS (#31), add option to include attributes from any other namespace (#28)</p>																			
		<p>..Reference attributes added (for elements that have existed in EAD3 already) ..Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>																			
		<p>localType changes (for element that have existed in EAD3 already and include @localtype there) - Apply camelCasing to @localType (#49) - Add the parallel attribute @localTypeDeclarationReference with data type IDREFS (#43)</p>																			
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	..Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOfElement, scriptOfElement	conventionDeclarationReference, maintenanceEventReference, sourceReference	localType, localTypeDeclarationReference	valueURI, vocabularySource, URI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduce mixed content (reference, span, referringString)	formatting-Extension	Context specific sub-elements	Shared	
odd	otherDescriptiveInfo	Y	Y	Y	Rename to otherDescriptiveInfo Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronolist, head, list, table Remove nesting, i.e. remove odd as sub-element Remove @encodinganalog	#57; #59; #62; #66; #49; #37	Y	Y	Y	Y					Y			Y	Y		
originalsloc	(formAvailable)				Remove originalsloc, see Transformations tab for more details	#65; #60; #57; #59; #62; #49; #74; #37															
origination	(agent)				Remove origination, see Transformations tab for more details	#58; #68															
otheragencycode	otherAgencyCode	Y		Y	Make sure otherAgencyCode appears only after all instances of agencyName Add @status Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog	#32; #37; #49	Y	Y		Y	Y	Y	Y	Y	Y				Y		
otherfindaid	otherFindAid	Y	Y	Y	Apply camelCasing Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronolist, head, list, table Add relations as an optional, not repeatable sub-element Remove archref and brief as direct sub-elements Remove nesting, i.e. remove otherfindaid as sub-element Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog	#69; #57; #59; #62; #49; #46; #74; #37	Y	Y	Y	Y	Y	Y	Y	Y			Y	Y			
otherrecordid	otherRecordid	Y		Y	Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog	#32; #37; #49	Y	Y		Y	Y			Y	Y				Y		
p	p	Y	Y		Add reference, referringString, and span as optional and repeatable sub-elements Remove abbr, expan, emph, foreign, lb, ptr, ref, date, footnote, num, quote, corpname, famname, function, genreform, geogname, name, occupation, persname, subject, title, and list Remove @encodinganalog Remove @identifier, @source, and @rules	#47	Y	Y	Y					Y	Y	Y	Y		Y (requires update in EAC-CPF)		
part	part	Y	Y	Y	Remove abbr, expan, emph, foreign, lb, ptr, ref, and date from part Require content in part (can't be left empty) Remove @encodinganalog Remove @identifier, @source, and @rules Remove persname, see Transformations tab for more details	#13; #70	Y	Y	Y	Y				Y	Y				Y		
persname	(agent) (referringString)				Remove persname, see Transformations tab for more details	#58; #68; #63															
physdesc	physDesc	Y	Y	Y	Apply camelCasing Add reference, span, and referringString as optional and repeatable sub-elements Remove abbr, expan, emph, foreign, lb, ptr, ref Remove @encodinganalog and @label	#49; #40; #63; #71; #38; #37	Y	Y	Y	Y				Y	Y	Y	Y				
physdescset	physDescSet	Y	Y		Apply camelCasing to physDescSet and its sub-element physDescStructured Remove @encodinganalog and @label Remove @coverage (see #109)	#49; #38; #37	Y	Y	Y					Y				Y			
physdescstructured	physDescStructured	Y	Y		Apply camelCasing Apply camelCasing to sub-elements unitType, physFacet, and descriptiveNote Apply camelCasing to attribute @physDescStructuredType, remove predefined values and make the attribute optional only Remove @otherphysdescstructuredtype Remove @encodinganalog and @label	#49; #38; #37; #1; #28	Y	Y	Y					Y	Y			Y			
physfacet	physFacet	Y	Y	Y	Add reference, span, and referringString as optional and repeatable sub-elements Remove abbr, emph, expan, foreign, lb, ptr, ref, corpname, famname, function, genreform, geogname, name, occupation, persname, subject, title, date, footnote, num, quote Replace @identifier with @valueURI and @source with @vocabularySource Add @vocabularySourceURI Remove @rules (replaced by @conventionDeclarationReference) Remove @encodinganalog	#70; #40; #63; #71; #72	Y	Y	Y	Y	Y			Y	Y	Y	Y				
physloc	physLoc	Y	Y	Y	Apply camelCasing Add reference, span, and referringString as optional and repeatable sub-elements Remove abbr, emph, expan, foreign, lb, ptr, ref Remove @encodinganalog, @label, and @parent	#49; #40; #63; #71; #38; #37	Y	Y	Y	Y				Y	Y	Y	Y				
phystech	physicalOrTechnicalRequirements	Y	Y	Y	Rename to physicalOrTechnicalRequirements Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronolist, head, list, table Remove nesting, i.e. remove odd as sub-element Remove @encodinganalog	#57; #59; #62; #66; #49; #37	Y	Y	Y	Y				Y			Y	Y			
	place				Add place Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y	Y			Y					Y	Y (requires update in EAC-CPF)	
	placeName				Add placeName Allow for the attributes as indicated in columns I to O and Q		Y	Y		Y	Y			Y	Y	Y			Y		
	placeRole				Add placeRole Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y		Y			Y	Y	Y			Y		

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @attender (#36), rename @lang to @languageOElement and relax data type from NMTOKEN to token (#53; #59), rename @script to @scriptOElement and relax data type from NMTOKEN to token (#50; #59), add @target with new data type IDREFS (#31) add option to include attributes from any other namespace (#28)</p> <p>..Reference attributes added (for elements that have existed in EAD3 already) ..Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>																				
		<p>localType changes (for element that have existed in EAD3 already and include @localType there) - Apply camelCasing to @localType (#39) - Add the parallel attribute @localTypeDeclarationReference with data type IDREFS (#43)</p>				Attributes in EAD 4.0										Content models in EAD 4.0						
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	..Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOElement, scriptOElement	conventionDeclarationReference, maintenanceEventReference, sourceReference	localType, localTypeDeclarationReference	valueURI, vocabularySource, vocabularySourceURI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduced content (reference, span, referringString)	mixed	formatting-Extension	Context specific sub-elements	Shared	
	places				Add places Allow for the attributes as indicated in columns I to O and Q	#96	Y	Y	Y	Y					Y						Y	
	placeType				Add placeType Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y		Y				Y	Y					Y (requires update in EAC-CPF)	
prefercite	preferCite	Y	Y	Y	Apply camelCasing Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove prefercite as sub-element Remove @encodinganalog	#57; #59; #62; #49; #37	Y	Y	Y	Y				Y					Y	Y		
processinfo	processInfo	Y	Y	Y	Apply camelCasing Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove processinfo as sub-element Remove @encodinganalog	#57; #59; #62; #49; #37	Y	Y	Y	Y				Y					Y	Y		
ptr	(reference)				Remove ptr, see Transformations tab for more details	#40; #45																
ptrgrp	@target				Remove ptrgroup, see Transformations tab for more details	#67																
publicationstatus	@publicationStatus				Turn publicationstatus into control@publicationStatus, see Transformations tab for more details	#32															Y	
publicationstmt	(findAidDesc)				Remove publicationstmt, see Transformations tab for more details	#27																
publisher	(findAidDesc)				Remove publisher, see Transformations tab for more details	#27																
quantity	quantity	Y	Y		Remove @encodinganalog	#37	Y	Y	Y					Y	Y							
quote	(referringString)				Remove quote, see Transformations tab for more details	#63																
recordid	recordId	Y			Require content in <recordId> (can't be left empty) Remove @encodinganalog and @stanconf	#32; #37; #49	Y	Y						Y	Y						Y	
ref	reference	Y	Y		Note: ref is the only element which already included @target in EAD3; for reference in EAD 4.0 only the data type is change from IDREF to IDREFS		Y	Y	Y			Y		Y	Y		Y (without reference)				Y	
	referringString				Add referringString Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y	Y			Y	Y						Y (requires update in EAC-CPF)	
relatedmaterial	relatedMaterial	Y	Y	Y	Apply camelCasing Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Add relations as an optional, not repeatable sub-element Remove archref and bibref as direct sub-elements Remove nesting, i.e. remove relatedmaterial as sub-element Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog	#59; #57; #59; #62; #49; #46; #72; #37	Y	Y	Y	Y	Y			Y					Y	Y		
relation	relation	Y	Y		Replace relationentry with targetEntity Replace datesingle with date and apply camelCasing to dateRange and dateSet Replace geogname with place and make that repeatable Add relationType, targetRole, targetType as optional and repeatable sub-elements Apply camelCasing to descriptiveNote and objectXMLWrap Change sequence of sub-elements by moving objectXMLWrap to the end (after descriptiveNote) Remove @relationtype (used as a basis for further transformation steps depending on the value used, see Transformations tab for details) Remove @otherrelationtype, @encodinganalog, @lastdateimeverified	#33; #69	Y	Y	Y					Y	Y					Y	Y	
relationentry	targetEntity	Y	Y		Replace relationentry with targetEntity Add required sub-element part (which can't be empty) Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @localtype, @encodinganalog, and @transliteration (replaced by @conventionDeclarationReference)	#33; #69	Y	Y	Y	Y				Y					Y	Y		
relations	relations	Y	Y		Add descriptiveNote as optional, not repeatable sub-element Remove @localtype and @encodinganalog	#33; #69	Y	Y	Y				Y	Y		Y			Y	Y		
	relationType				Add relationType Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y				Y	Y						Y	
repository	(agent)				Remove repository, see Transformations tab for more details	#58; #68																
representation	(findAidDesc)				Remove representation, see Transformations tab for more details	#32															Y (requires update in EAC-CPF)	
rightsdeclaration	rightsDeclaration	Y			Replace sbr with shortCode and citation with reference Change order of sub-elements so that reference comes first, followed by shortCode and descriptiveNote Apply camelCasing to sub-element descriptiveNote Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog and @localtype	#32; #37; #49	Y	Y		Y				Y					Y	Y	Y	
row	(formattingExtension)				Remove row, see Transformations tab for more details	#62																
scopecontent	scopeContent	Y	Y	Y	Apply camelCasing Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Remove nesting, i.e. remove scopecontent as sub-element Remove @encodinganalog	#57; #59; #62; #49; #37	Y	Y	Y	Y				Y					Y	Y		

<p>Note: This sheet shows the changes applied to each element in terms of its definition within the EAD schema. This also includes the addition of new elements. The sheet "Transformations", on the other hand, shows the changes that would need to be applied to each existing element in order to move it from EAD3 to EAD 4.0.</p> <p>= not available in EAD 4.0 anymore (removed, replaced or combined) = new in EAD 4.0</p>		<p>General change for attributes (applicable to all elements that have existed in EAD3 already): Remove predefined values for @audience (#1), remove @altrender (#36), rename @lang to @languageOIElement and relax data type from NMTOKEN to token (#53; #59), rename @script to @scriptOIElement and relax data type from NMTOKEN to token (#59; #59), add @target with new data type IDREFS (#31), add option to include attributes from any other namespace (#28)</p>																			
		<p>..Reference attributes added (for elements that have existed in EAD3 already) Add @conventionDeclarationReference, @maintenanceEventReference, and @sourceReference all with data type IDREFS (#11)</p>																			
		<p>localType changes (for element that have existed in EAD3 already and include @localtype there) - Apply camelCasing to @localtype (#49) - Add the parallel attribute @localTypeDeclarationReference with data type IDREFS (#43)</p>																			
Element in EAD3 (deprecated)	Element in EAD 4.0	General change for attributes applied	..Reference attributes added	localType changes applied	Change description	GitHub issue(s)	audience, id, target	languageOIElement, scriptOIElement	conventionDeclarationReference, maintenanceEventReference, sourceReference	localType, localTypeDeclarationReference	valueURI, vocabularySource, vocabularySourceURI	href, linkRole, linkTitle	base	Context-specific attributes	Other namespace	Text	Reduced mixed content (reference, span, referringString)	formatting-Extension	Context specific sub-elements	Shared	
script	writingSystem	Y	Y		Rename to writingSystem Apply camelCasing to @scriptCode; also change data type from NMTOKEN to token Remove @label and @encodinganalog	#38; #37; #36; #23	Y	Y	Y					Y	Y	Y				Y	
separatedmaterial	separatedMaterial	Y	Y	Y	Apply camelCasing Add abstract as an optional, not repeatable sub-element Add a choice between p (optional, repeatable) and the new element formattingExtension (optional, not repeatable) for more detailed text formatting Remove formatting elements blockquote, chronlist, head, list, table Add relations as an optional, not repeatable sub-element Remove archref and bhref as direct sub-elements Remove nesting, i.e. remove separatedmaterial as sub-element Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog	#69; #57; #59; #52; #49; #46; #72; #37	Y	Y	Y	Y	Y				Y			Y	Y		
seriesstmt	(findAidDesc)				Remove seriesstmt, see Transformations tab for more details	#27															
source	source	Y			Replace sourceentry with reference and make it a required (and repeatable) sub-element Add citeRange as a new optional and repeatable sub-element (to appear before descriptiveNote if both exist) Apply camelCasing to sub-elements descriptiveNote and objectXMLWrap and change their order (descriptiveNote first, objectXMLWrap second) Apply camelCasing to @linkRole and @linkTitle Remove @actual, @arcrole, @getow Add @valueURI, @vocabularySource, @vocabularySourceURI Remove @encodinganalog and @lastdatimeverified	#27; #32; #49; #39; #37	Y	Y			Y	Y			Y				Y	Y	
sourceentry	(reference)				Remove sourceentry, see Transformations tab for more details	#32							Y		Y				Y	Y	
sponsor	(agent)				Remove sponsor, see Transformations tab for more details	#27															
subject	subject	Y	Y	Y	Replace the required and repeatable sub-element part with the required and repeatable sub-element term Add an optional choice between date, dateRange, and dateSet Add placeName, targetType, targetRole, and relationType as optional and repeatable sub-elements Add descriptiveNote as optional, not repeatable sub-element Replace @identifier with @valueURI and @source with @vocabularySource Add @vocabularySourceURI Remove @rules (replaced by @conventionDeclarationReference) Remove @normal Remove @relator (replaced by targetRole) Remove @encodinganalog	#67; #63; #69	Y	Y	Y	Y	Y			Y						Y	
subtle	(title)				Remove subtle, see Transformations tab for more details	#27															
table	(formattingExtension)				Remove table, see Transformations tab for more details	#62															
	targetRole				Add targetRole Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y	Y				Y	Y				Y	
	targetType				Add targetType Allow for the attributes as indicated in columns I to O and Q		Y	Y	Y	Y	Y				Y	Y				Y (requires update in EAC-CPF)	
tbody	(formattingExtension)				Remove tbody, see Transformations tab for more details	#62															
term	term	Y	Y		Remove @encodinganalog, @transliteration, @lastdatimeverified Remove @source, @rules, @identifier	#37; #34; #39; #13	Y	Y	Y						Y	Y				Y	
tbody	(formattingExtension)				Remove tbody, see Transformations tab for more details	#62															
thead	(formattingExtension)				Remove thead, see Transformations tab for more details	#62															
title	title (publicationNote) (referringString)	Y	Y	Y	Only applicable when title is used as sub-element of the new findAidDesc element: Replace @identifier with @valueURI and @source with @vocabularySource Add @vocabularySourceURI Remove @rules (replaced by @conventionDeclarationReference) Remove @normal Remove @relator Remove @encodinganalog Replace @render (respectively @altrender) with @style If title is used as sub-element of controlaccess, indexentry, or namegrp, or as a mixed content element, see Transformations tab for more details	#27; #13; #63; #67	Y	Y	Y	Y			Y	Y					Y		
titleproper	(title)				Remove titleproper, see Transformations tab for more details	#27															
titlestmt	(findAidDesc)				Remove titlestmt, see Transformations tab for more details	#27															
today	toDate	Y	Y	Y	Apply camelCasing to toDate and its attributes @standardDate, @notAfter, and @notBefore	#4	Y	Y		Y				Y	Y	Y				Y	
unitdate	unitDate	Y	Y	Y	Apply camelCasing Add reference, span, and referringString as optional and repeatable sub-elements Remove abbr, emph, expan, foreign, lb, ptr, ref Apply camelCasing to the attributes @unitDateType and @dateChar Add @notAfter, @notBefore, and @status Replace @normal with @standardDate Remove @encodinganalog and @label	#49; #40; #63; #71; #38; #37; #68	Y	Y	Y					Y	Y	Y	Y				
unitdatestructured	unitDateStructured	Y	Y		Apply camelCasing Apply camelCasing to the sub-elements dateRange and dateSet Replace sub-element datesingle with date Apply camelCasing to the attributes @unitDateType and @dateChar Remove @encodinganalog and @label	#49; #4; #36; #37	Y	Y	Y					Y	Y					Y	

